



CEWELD AA CuAl14Fe

TYPE Copper-Aluminum GMAW composite welding wire for cladding applications.

ANWENDUNGEN Cladding components undergoing metal to metal wear with high friction and or heavy surface loads on top of cast iron, steels and or bronzes.

EIGENSCHAFTEN

- Special alloyed copper composite wire suitable for the Mig process• The weld metal is a Cu-Al bronze with extreme high aluminium content.
- Sound, pore free deposits with excelent sliding properties and low friction.

KLASSIFIKATION EN ISO 14700: T Cu1

GEEIGNET FÜR CuAl14Fe

ZULASSUNGEN

SCHWEISSPOSITIONEN



**TYPISCHE CHEMISCHE
ANALYSE DES
SCHWEISSMETALLS (%)**


C	Fe	Cu	Al
0.2	4	Rem.	13.5

MECHANISCHE GÜTEWERTE

Heat Treatment	R _{p0,2} (MPa)	R _m (MPa)	A ₅ (%)	Hardness
As Welded				420 HB

RÜCKTROCKNUNG Not required

GAS ACC. EN ISO 14175 I1, I3



CEWELD AA CuAl14Fe

AA CUAL14FE 1,6MM

Packaging	KG/unit	EanCode
D-300	13	8720663408990