

# CEWELD SP ZnAl 85/15

|                                                |                                                                                                                                                 |                   |    |    |    |  |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|----|----|----|--|
| TYPE                                           | Solid metal spray wire                                                                                                                          |                   |    |    |    |  |
| ANWENDUNGEN                                    | In case high corrosion resistance is required                                                                                                   |                   |    |    |    |  |
| EIGENSCHAFTEN                                  | High corrosion resistance                                                                                                                       |                   |    |    |    |  |
| KLASSIFIKATION                                 | EN ISO                                                                                                                                          | 14919: 2.3 (ZnAl) |    |    |    |  |
| GEEIGNET FÜR                                   | Metal spray wire for so called Scooping in case high corrosion resistance is required. Bridges, outdoor steel furniture, monopiles, wind mills. |                   |    |    |    |  |
| ZULASSUNGEN                                    |                                                                                                                                                 |                   |    |    |    |  |
| SCHWEISSPOSITIONEN                             |                                                                |                   |    |    |    |  |
| TYPISCHE CHEMISCHE ANALYSE DES FÜLLMETALLS (%) | <table><tr><td>Zn</td><td>Al</td></tr><tr><td>85</td><td>15</td></tr></table>                                                                   | Zn                | Al | 85 | 15 |  |
| Zn                                             | Al                                                                                                                                              |                   |    |    |    |  |
| 85                                             | 15                                                                                                                                              |                   |    |    |    |  |
| MECHANISCHE GÜTEWERTE                          |                                                                                                                                                 |                   |    |    |    |  |
| RÜCKTROCKNUNG                                  | Not required                                                                                                                                    |                   |    |    |    |  |
| GAS ACC. EN ISO 14175                          |                                                                                                                                                 |                   |    |    |    |  |