


CEWELD MA 650

TYPE	Massieve lasdraad voor het hardoplassen en herstellen van versleten onderdelen.						
TOEPASSINGEN	Hardoplassen of herstellen van versleten onderdelen die bestand moeten zijn tegen hoge slijtage en gemiddelde impact.						
EIGENSCHAPPEN	Massieve lasdraad voor het hardoplassen van onderdelen die onderhevig zijn aan hoge slijtage. De toevoeging van wolfraam, vanadium en molybdeen zorgt voor betere snij-eigenschappen en een hogere hardheid. Hardheid: 570-660 HB						
CLASSIFICATIE	AWS	A 5.21: ERFe-8					
	EN ISO	14700: S Fe8					
	DIN	8555: MSG 3-GZ-60-T					
	W.Nr.	1.2606					
	F-nr	71					
GESCHIKT VOOR	Mixer blades, cutting knives, pumps, loader teeth, screws, sludge disposal, carbidge recycling etc.						
GOEDKEURINGEN							
LASPOSITIES	 PA  PB  PC  PF						
TYPICAL CHEMICAL ANALYSIS OF THE FILLER METAL (%)	C	Mn	Cr	Mo	V	Fe	W
	0.4	0.5	5	1.4	0.3	Rem.	1.3
MECHANISCHE WAARDEN	Heat Treatment		R _{P0,2} (MPa)	R _m (MPa)	A5 (%)	Hardness	
	As Welded					60 HRc	
HERDROGEN	Not required						
GAS ACC. EN ISO 14175	M21						



CEWELD MA 650

MA 650 1,0MM

Packaging	KG/unit	EanCode
BS-300	15	8720663403148

MA 650 1,2MM

Packaging	KG/unit	EanCode
BS-300	15	8720663403155